

SG2KTL-S/SG3KTL-S

String Inverter

**Flexible**

- Dual MPPT, compatible with different residential rooftop system design(Only - D series products)
- Max. input voltage 600V, compatible with different PV panel and string design

**Easy**

- Only 9 kg of 3 kW inverter, easy to handle and install
- Easy replacement and transportation, reduce the trouble of service

**Intelligent**

- Intelligent Wi-Fi communication, flexible for various applications
- Intelligent local access via the APP, convenient to view the data any time
- Intelligent cloud monitoring to enable the centralized operation, management and maintenance

**Qualified**

- TÜV, CE, AS4777, AS/NZS 3100, VDE AR N 4105, KTC certification



Input Side Data	SG2KTL-S	SG 3KTL-S
Max. PV input power	3000W	4000W
Max. PV input voltage	600V	
Startup voltage	120V	
Nominal input voltage	360V	
MPP voltage range	110 - 560V	
MPP voltage range for nominal power	210 - 480V	310 - 480V
No. of MPPTs	1	
Max. number of PV strings per MPPT	1	
Max. PV input current	10A	
Max. current for input connector	12A	
Output Side Data		
Nominal AC output power	2000W	3000W
Max AC output power@PF=1.0	2000W	3000W
Max. AC output apparent power	2000VA	3000VA
Max. AC output current	9.1A	13.6A
Nominal AC voltage	220Vac, 230Vac (Single phase)	
AC voltage range	180 - 276Vac (May vary as per corresponding country's grid standard)	
Nominal grid frequency	50Hz/60Hz	
Grid frequency range	45 - 55Hz/55 - 65Hz (May vary as per corresponding country's grid standard)	
THD	< 3 % (Nominal power)	
DC current injection	<0.5 %In	
Power factor	>0.99 @ default value at nominal power, (adj. 0.8 leading - 0.8 lagging)	
Protection		
Anti-islanding protection	Yes	
LVRT	No	
DC reverse connection protection	No	
AC short circuit protection	Yes	
Leakage current protection	Yes	
DC switch	Optional	
DC fuse	No	
Overshoot protection	Varistors	
System Data		
Max. efficiency	97.40%	97.50%
Max. European efficiency	96.60%	97.00%
Isolation method	Transformerless	
Ingress protection rating	IP65	
Night power consumption	<1W	
Operating ambient temperature range	-25 to 60°C (>45°C derating)	
Allowable relative humidity range	0 -100%	
Cooling method	Natural cooling	
Max. operating altitude	2000m	
Display	LED indicator, LCD (optional, see communication options below)	
Communication	Optional: eShow (LCD), eShow+ (LCD + Wi-Fi), ZE100 (LCD + Wi-Fi + energy meter for zero-export), GPRS (for China & Europe), Remark: Built-in earth fault alarm on eShow, eShow+ and ZE100	
DC connection type	MC4	
AC connection type	Plug and play connector	
Certification	IEC61000-6-2, IEC61000-6-3 □ AS/NZS3100, AS4777.2 , AS4777.3 , IEC62109-1, IEC62109-2, VDE-AR-N-4105, VDE0126-1-1, G83/2/G59/3, C10/11, EN50438□NB/T 32004, GB/T29319□KS C8564:2015;; CE, CGC, TUV, SAA, KTC	
Mechanical Data		
Dimensions (W*H*D)	300*370*125 mm	
Mounting method	Wall-mounting bracket	
Weight	9kg	

Efficiency Curve

